

Dept

Qty

DC

1

ED

1

IE

1

ISO

1

PD

1

R&D

1

SD

1

QA

1

QC

1

QE

1

Assembled

A Lock Nut

B Washer

C Body

D Seal

E Claw

F Sealing Nut

Model	Cable Range (mm)	Thread O.D. L1(mm)	Thread Length L2(mm)	Joint length H(mm)	Spanner Size(mm)
PG7	3~6.5	12.5	7	19	14
PG9	4~8	15.2	8	20	18
PG11	5~10	18.6	8	21	20/21
PG13.5	6~12	20.4	8	22	22
PG16	10~14	22.5	9	23	24
PG19S	10~14	25	9	25	24/27
PG19	8~16	25	9	25	27
PG21	13~18	28.3	9	27	30/32
PG21S	9~16	28.3	9	27	30/32
PG25	15~22	32	10	29	35
PG29	18~22	37	11	31	40
PG36	25~33	47	12	37	50
PG42	32~38	54	13	38	57
PG48	37~44	59.3	14	38	64
PG63	42~52	72	15	42	78

Notes:

Specifications:

1. Temperature: -40°C~+100°C.

Materials:

1. Material:Parts A,C,F are made of Brass;Part E are made of Nylon;

Parts B and D are made of NBR.

Product Number Code:

DS1170-06 - X X X

Seal color

B: Black

Plating type

N: Nickel

Model

PG7 PG9 PG9

.....

PG42 PG48 PG63

GENERAL TOLERANCE

ANGLE TOLERANCE

PROJECTION

TITLE

UNITS

SHEET SIZE

DRAWING TYPE

CUSTOMER

SCALE

DRAWING NO.

1:1

SHEET

1 OF 2

C-DS1170-06-XXX-A

Projection symbol

mm

A4

SERIES

DS1170-06 SERIES

晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD

Series Image-Reference Only

1

2

3

4

5

6

7

8

Dept

Qty

DC

ED

IE

ISO

PD

R&D

SD

QA

QC

QE