


Dept / Qty	
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1


The information provided herein is from CONNFLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how are owned exclusively by CONNFLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNFLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNFLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.


Male











REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 10/16/24'		
B	Drawing Update	WPY 07/23/26'		
C	Drawing Update	WPY 10/29/26'		

Notes:

1. Rated current: 35A(12AWG)
2. Contact resistance: ≤0.55mΩ
3. Insulation resistance: ≥2000MΩ
4. Dielectric Withstanding Voltage: 1000 VAC/1 min
5. Insertion and extraction force: 1.8~4.5 kgf
6. Durability: 100 cycles
7. Operating temperature: -20℃~+120℃
8. Protection level: IP40
9. Salt spray: 24 hours

Materials:

1. Insulator: PA,UL94 V-0
2. Contact: Copper alloy

Product Number Code:

DS1220-02- X X X X X - X

- Plating Level: B:Level B 3A:Level 3A
- Logo Type: X:W/O Logo N/A:W/Logo
- Housing color: Y:Yellow B:Black
- Contact Plating 8:Full gold flash
- Connector type: M:Male F:Female A:Male+Female
- No. of Contacts 2:2Pin

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 2
DRAWING NO.	C-DS1220-02-XXXXX-C		

PROJECTION		TITLE	DCXT60U-M Solder Type
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1220-02 SERIES


晨翔电子有限公司


CONNFLY ELECTRONIC CO. LTD


Dept / Qty	
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1


The information provided herein is from CONNFLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, is solely owned exclusively by CONNFLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNFLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNFLY may enforce its intellectual property rights at its own discretion; failures or delays to exercise such rights does not constitute a waiver of such rights.

Female









REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	WPY 10/16/24'		
B	Drawing Update	WPY 07/23/26'		
C	Drawing Update	WPY 10/29/26'		

Notes:

1. Rated current: 35A(12AWG)
2. Contact resistance: ≤0.55mΩ
3. Insulation resistance: ≥2000MΩ
4. Dielectric Withstanding Voltage: 1000 VAC/1 min
5. Insertion and extraction force: 1.8~4.5 kgf
6. Durability: 100 cycles
7. Operating temperature: -20℃~+120℃
8. Protection level: IP40
9. Salt spray: 24 hours


Materials:

1. Insulator: PA,UL94 V-0
2. Contact: Copper alloy

Product Number Code:

DS1220-02- X X X X X - X

- Plating Level: B:Level B 3A:Level 3A
- Logo Type: X:W/O Logo N/A:W/Logo
- Housing color: Y:Yellow B:Black
- Contact Plating 8:Full gold flash
- Connector type: M:Male F:Female A:Male+Female
- No. of Contacts 2:2Pin



GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	2 OF 2
DRAWING NO.	C-DS1220-02-XXXXX-C		

PROJECTION		TITLE	DCXT60U-F Solder Type
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1220-02 SERIES

晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD