



Dept	Qty
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QF	1

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or reproduction of any part of this document is strictly prohibited. CONNELY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.



(Series Image-Reference Only)

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 01/09/18'		

Notes:
 Specifications:
 1. Contact Resistance: 20mΩ Max.
 2. Insulation Resistance: 1000MΩ Min.
 3. Dielectric Withstanding Voltage: 600V AC(rms) For 1 Minute.
 4. Current Rating:3A.
 5. Temperature: -40°C~+105°C.
 Materials:
 1. Contact Material: Copper Alloy.
 2. Contact Plating: Gold Plating Over Nickel.
 3. Insulator Materials: PBT,Black,UL94-V0.

Product Number Code:
 DS1023-41 - X X X X X X
 Packing type
 T: Tray
 Housing color
 B: Black
 Contact plating
 8: Full gold flash
 Mounting type
 V: Vertical Through
 Connector type
 S: Socket
 No.of contacts
 2x2 - 2x20

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	2.54mm Female Header V/T H=7.1mm Big Window Type					
X.	±0.60	X.	±5°	UNITS	mm	SHEET SIZE	A4	SERIES	DS1023-41 SERIES			
.X	±0.38	.X	±3°	晨翔电子有限公司 CONNELY ELECTRONIC CO. LTD								
.XX	±0.25	.XX	±2°									
DRAWING TYPE		CUSTOMER		晨翔电子有限公司 CONNELY ELECTRONIC CO. LTD								
SCALE		1:1								SHEET	1 OF 1	
DRAWING NO.		C-DS1023-41-XXXXXX-A										